Serial No. : 10/664,822

Filed : September 16, 2003

Page : 2 of 15

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A fuel cartridge that supplies a source of fuel to a direct

methanol fuel cell, the fuel cartridge comprising:

a housing;

a fuel egress coupled to the housing to allow contents in the housing to escape from the

housing through the fuel egress port; and

a surface area enhanced planar vaporization membrane residing in the fuel cartridge.

(Original) The fuel cartridge of claim 1 wherein the surface area enhanced planar

vaporization membrane is a polymer membrane disposed about a substantial portion of an

interior of the housing to provide a high surface area membrane.

3. (Currently Amended) The fuel cartridge of claim 1 wherein the surface area enhanced

planar vaporization membrane is a composite membrane comprised of multiple layers or folds of

polymer membrane to increase vapor permeation surface area.

4. (Original) The fuel cartridge of claim 1 wherein the surface area enhanced planar

vaporization membrane is a membrane arranged as a series of folds.

5. (Original) The fuel cartridge of claim 1 wherein the surface area enhanced planar

vaporization membrane is a polymer membrane provided with macroscopically irregular and/or

microscopically roughened membrane surfaces to increase the effective membrane surface area

for vaporization.

Serial No.: 10/664,822

Filed September 16, 2003

Page : 3 of 15

6. (Original) The fuel cartridge of claim 1 wherein the surface area enhanced planar vaporization membrane spaces a liquid source of oxidizable fuel from a vapor phase of the source of oxidizable fuel.

- 7. (Original) The fuel cartridge of claim 1 wherein the cartridge contains a liquid source of oxidizable fuel and/or a carbonaceous compound or mixture of such compounds.
- 8. (Original) The fuel cartridge of claim 1 wherein the liquid source of oxidizable fuel is methanol.
- 9. (Original) The fuel cartridge of claim 1 wherein the enhanced planar vaporization membrane is comprised of a polymer material selected from the group consisting of polyurethanes, silicones, poly(trimethylsilyl-propyne), polymeric compositions, and composites.
- 10. (Original) The fuel cartridge of claim 1 wherein the surface area enhanced planar vaporization membrane enhances a delivery rate of methanol in a vapor phase to the egress port for a given cartridge size.
- 11. (Original) A fuel cartridge that supplies a source of fuel to a direct methanol fuel cell, the fuel cartridge comprising:
  - a housing;
  - a fuel egress port supported by the housing; and
  - a composite membrane residing in the fuel cartridge comprising:
  - a porous substrate;
  - a polymer membrane disposed over a first surface of the porous substrate; and
- a coating of a methanol-impermeable material disposed over an opposite surface of the substrate.

Serial No. : 10/664,822

Filed : September 16, 2003

Page : 4 of 15

12. (Original) The fuel cartridge of claim 11 wherein substrate is provided to hold methanol in a liquid state within the porous material to enable liquid methanol to migrate to the polymer membrane and convert to a vapor phase.

- 13. (Original) The fuel cartridge of claim 11 wherein the composite membrane is wound into a cylindrical shaped element.
- 14. (Original) The fuel cartridge of claim 11 wherein gaps between the polymer membrane and the methanol-impermeable coating providing a path for transporting a high flux of methanol vapor to the egress port.
- 15. (Original) The fuel cartridge of claim 11 wherein a plurality of the composite membranes are disposed in the fuel cartridge.
- 16. (Original) The fuel cartridge of claim 11 wherein a plurality of the composite membranes are disposed in the fuel cartridge and wound into a cylindrical shaped element.
- 17. (Original) The fuel cartridge of claim 11 wherein the substrate is polyethylene, polypropylene, nylon, polyurethane, or other analogous polymers or composites of one or more of these polymers.
- 18. (Original) The fuel cartridge of claim 11 wherein the polymer membrane is a polyurethane material.
- 19. (Currently Amended) The fuel cartridge of claim 11.48 wherein the polymer material is selected from the group consisting of polyurethanes, silicones, poly(trimethylsilyl-propyne), polymeric compositions, and composites.

Serial No. : 10/664,822

Filed : September 16, 2003.

Page : 5 of 15

20. (Original) The fuel cartridge of claim 18 wherein the polymer has a microporosity characteristic to govern vaporization.

- 21. (Original) The fuel cartridge of claim 11 wherein the membrane is a sintered metal disc coated with a polymer.
- 22. (Currently Amended) The fuel cartridge of claim 11 wherein the methanol-impermeable coating is a isa cross-linked rubber, a polymer/inorganic composite, a surface fluorinated high density polyethylene, or other methanol-impermeable material.
- 23. (Currently Amended) The fuel cartridge of claim 11 wherein the substrate is polyethylene, polypropylene, nylon, polyurethane, or other analogous polymers or composites of one or more of these polymers; the polymer membrane [[is]] is a polyurethane[[s]], a silicone[[s]], poly(trimethylsilyl-propyne), or composites of polyurethanes, silicones, poly(trimethylsilyl-propyne) and the methanol-impermeable coating is a cross-linked rubber, a polymer/inorganic composite, a surface treated material such as surface fluorinated high density polyethylene, or other methanol-impermeable material.
- 24. (Currently Amended) A composite membrane residing in the fuel eartridge comprising:
  - a porous substrate;
  - a polymer membrane disposed over a first surface of the porous substrate; and a coating of a methanol-impermeable material disposed over an opposite surface of the substrate.
  - 25. (Original) The membrane of claim 24 wherein substrate is provided to hold methanol in a liquid state within the porous material to enable liquid methanol to migrate to the polymer membrane and convert to a vapor phase.

Serial No. : 10/664,822

Filed September 16, 2003

Page : 6 of 15

26. (Original) The membrane of claim 24 wherein the composite membrane is wound into a cylindrical shaped element.

- 27. (Original) The membrane of claim 24 wherein gaps between the polymer membrane and the methanol-impermeable coating providing a path for transporting a high flux of methanol vapor.
- 28. (Original) The membrane of claim 24 wherein the substrate is polyethylene, polypropylene, nylon, polyurethane, or other analogous polymers or composites of one or more of these polymers.
- 29. (Original) The membrane of claim 24 wherein the polymer material is selected from the group consisting of polyurethanes, silicones, poly(trimethylsilyl-propyne), polymeric compositions, and composites.
- 30. (Currently Amended) The membrane of claim <u>24 wherein</u> the polymer has a microporosity characteristic to govern vaporization.
- 31. (Original) The membrane of claim 24 wherein the membrane is a sintered metal disc, coated with a polymer.
- 32. (Original) The membrane of claim 24 wherein the methanol-impermeable coating is a cross-linked rubber, a polymer/inorganic composite, a surface fluorinated high density polyethylene, or other methanol-impermeable material.
- 33. (Original) The membrane of claim 24 wherein the substrate is polyethylene, polypropylene, nylon, polyurethane, or other analogous polymers or composites of one or more of these polymers; the polymer membrane is polyurethanes, silicones, poly(trimethylsilyl-

Serial No.: 10/664,822

Filed : September 16, 2003

Page : 7 of 15

propyne), or composites of polyurethanes, silicones, poly(trimethylsilyl-propyne) and the methanol-impermeable coating is a cross-linked rubber, a polymer/inorganic composite, a surface treated fluorinated high density polyethylene.

34. (Withdrawn) An arrangement comprises:

a direct methanol fuel cell;

a fuel cartridge that supplies a source of fuel to the direct methanol fuel cell, the fuel cartridge comprising:

a housing;

a fuel egress port supported by the housing; and

a surface area enhanced planar vaporization membrane residing in the fuel cartridge and

a fuel reservoir that receives fuel from the fuel cartridge, the fuel reservoir arranged to deliver fuel to the fuel cell and the fuel reservoir comprising:

a housing; and

a surface area enhanced planar vaporization membrane residing in the fuel reservoir, which in combination with the surface area enhanced planar vaporization membrane residing in the fuel cartridge provides a dual stage vaporization of fuel to the fuel cell.

- 35. (Withdrawn) The arrangement of claim 34 wherein at least one of the surface area enhanced planar vaporization membranes is a polymer membrane disposed about a substantial portion of an interior perimeter of the housing to provide a high surface area membrane.
- 36. (Withdrawn) The arrangement of claim 34 wherein at least one of the surface area enhanced planar vaporization membranes is a composite membrane comprised of multiple layers or folds of polymer membrane to increase vapor permeation surface area.
- 37. (Withdrawn) The arrangement of claim 34 wherein at least one of the surface area enhanced planar vaporization membranes is a membrane arranged as a series of folds.

Serial No. 1 10/664,822

Filed: September 16, 2003

Page : 8 of 15

38. (Withdrawn) The arrangement of claim 34 wherein at least one of the surface area enhanced planar vaporization membranes is a polymer membrane provided with macroscopically irregular and/or microscopically roughened membrane surfaces to increase the effective membrane surface area for vaporization.

39. (Withdrawn) A method of operating an electronic device comprises:

arranging a fuel cartridge to supply a source of fuel to a direct methanol fuel cell, the fuel cartridge comprising:

- a housing;
- a fuel egress port supported by the housing; and
- a composite membrane residing in the fuel cartridge comprising:
- a porous substrate;
- a polymer membrane disposed over a first surface of the porous substrate; and
- a coating of a methanol-impermeable material disposed over an opposite surface of the substrate.